

DETAILED ESTIMATE SUNDRAPE ROLLER



Sidepull Roller Type 6210

for draperies see roller blinds collection
maximum sizes width min/max 400/2000 mm, height 3000
depending on the chosen drapery and the
direction of fabrication.

Roller blind shaft
extruded aluminium profile AlMgSi 0.5 F22, diameter 30 x 2 mm.

Sidepull gear
bead chain gear, integrated rolling down safety device, type plastic white or brown, inserted
in the roller shaft in a twist-safe way, drapery weight max 2 kg.

Roller casing
extruded aluminium profile AlMgSi 0.5 F22, E6/EV1 anodized, powder coated white RAL
9016 or brown RAL 8014, 2 parts, width 72 mm, height 70 mm, side parts made of plastic
white or brown, roller can be clicked in over clips nose.

Bottom rail
extruded aluminium profile AlMgSi 0.5 F22, width 5,5 mm, height 25 mm, inserted in drapery
seam.
For foil drapery: extruded aluminium profile 1 part with flat bar, width 8 mm, height 30 mm.

Control
continuous control by pulling the bead chain. Two chain locks serve as top and bottom end
position of the roller blind drapery.

Mounting
wall, ceiling, window niche. Screwed through back side of casing.

Variants
type 6211 with tension wire guiding. Fixing at wall/ceiling/window niche.
Tension wire nature coloured or white, alu bottom rail E6/EV1
anodized, powder coated white RAL 9016 or brown RAL 8014, 1 part,
open, fixing of drapery by inserted flat bar, also available with brush profile,
width 11 mm, height 41 mm.